

FLEXCUT[®] 125

PLASMA CUTTER



CLEAR CUT PERFORMANCE

The FlexCut™ 125 handles the toughest cutting jobs in construction, general fabrication, automation, and maintenance and repair. CNC-ready with built-in ports, automatic table detection, and machine torch compatibility, it integrates easily into automated systems. An industrial IP23-rated enclosure and rugged internal design ensure durability in demanding conditions. Compatible with our FlexConnect™ Torch System, giving you the flexibility to switch between torch heads or cables in seconds.

Processes »

Drag Cutting, Grid Cutting, Mechanized, Extended, Precision Cutting, Gouging and Marking

Applications »

Construction, Heavy Fabrication, Automation

Output »



Input »



Product Numbers »

K5828-H HANDHELD ASSEMBLY
K5828-M MECHANIZED ASSEMBLY
K5828-PS POWER SOURCE ONLY

Cut Performance - Mild Steel»




VALUE-ADDED FEATURES

- **125 Amps of Cutting Power:** Tackle thicker materials with confidence and precision.
- **High Duty Cycle:** Built for demanding applications without overheating or slowing down.
- **LCD Display:** Bright, easy-to-read screen with simple controls for quick and precise adjustments.
- **Plug-and-Play CNC Integration:** Seamless integration with CNC tables with automatic table detection for fast, precise setup—no extra kits required.
- **Multi-Process Capability:** Drag cutting, fine cutting, gouging, and marking with one machine for maximum versatility.
- **Rugged by Design:** Heavy-duty construction built for real-world conditions—hard to damage, and ready to withstand impact, dust, and daily wear.
- **Industrial IP23 Protection:** Resists dust and water spray for dependable performance in challenging conditions.

KEY CONTROLS

- | | |
|----------------------|-------------------------------|
| 1. Handle | 6. Remote Connection (14-pin) |
| 2. User Interface | 7. Input Power Cable |
| 3. Main Control Knob | 8. On/Off Switch |
| 4. Torch Connection | 9. Cooling Fan |
| 5. Work Connection | 10. Air Inlet |



USER INTERFACE

1. Amperage
2. Process
3. Adjust Air Pressure
4. Guided Cutting Setup
5. Advanced Settings
6. Gas Purge



GUIDED CUTTING SETUP

From power-on to precision cutting in seconds

Don't waste time with complicated setup. With FlexCut™, you're ready to cut in seconds.

1. Adjust machine amperage to recommended setting
2. **Select the Cutting Guide** icon on the main user interface.
3. **Enter your material type and thickness.**
4. **View the recommended cutting amperage**—automatically calculated for clean, precise results.



FLEXCUT PRO™ TORCH WITH FLEXCONNECT™

One Torch. Endless Flexibility.

Patented FlexConnect™ Torch System: Switch between torch heads or cables in seconds—no tools required.

Customizable Options: Choose from multiple torch heads and cable lengths to fit your application.

Universal Machine Compatibility: Use one torch across the entire FlexCut™ machine lineup—no need for separate torches for different systems

Lower Repair Costs: Replace only the damaged part—head or cable—without buying a whole new torch.



MORE CUTS. LESS COST. ZERO HASSLE.

Long-Life Consumables: Advanced electrode design and optimized airflow deliver more cuts per consumable, reducing replacement frequency and lowering operating costs.

Threadless Electrode Connection: No more seized threads—just smooth, quick changes every time.

Snap-In Installation: Tool-free design means you can replace consumables in seconds.



CNC INTEGRATION

Plug-and-Play CNC Integration: Built-in ports for easy setup - no extra kits required.

Automatic Table Detection: Fast, precise setup.

CNC Torch Options: Compatible with machine torches for automated cutting.



CUTTING SPECIFICATIONS

Recommended Cut Thickness / Speed	1 1/2 in / 15 ipm
Maximum Cut Thickness / Speed	1 3/4 in / 10 ipm
Severance Cut Thickness / Speed	2 1/4 in / 5 ipm
Pierce Thickness	1 in
Gouge Rate	14 lbs/hr



WHAT'S INCLUDED

		Handheld Package K5828-H	Mechanized Package K5828-M	Power Source Only K5828-PS
FlexCut® 1025 Plasma Cutter	N/A	•	•	•
FlexCut® PRO FlexConnect® Handheld Torch 25 ft	KP5850-25	•		
FlexCut® PRO FlexConnect® Mechanized Torch 25 ft	KP5852-25		•	
Air Filter	KP5844-1	•	•	•
Work Clamp & Cable	KP6035-1	•	•	•
Input Power Cord	N/A	•	•	•
Complete Consumable Kit - Handheld	KP5829-125	•		
Complete Consumable Kit - Mechanized	KP5830-125		•	

RECOMMENDED ACCESSORIES



Plasma Circle Cutting Guide Kit
For cutting circles 3-33in in diameter. Works with all Lincoln Electric FlexCut PRO torches
Order KP5916-1

Plasma Straight & Angle Cutting Kit
Guide for making straight cuts with any plasma cutting torch
Order KP5917-1



OMNISHield™ Face Shield
Shade 5 IR lens provides infrared light protection for plasma cutting applications
Order K3754-1



FlexCut PRO FlexConnect Torch
Includes 25 ft torch cable and Lincoln Electric's patented handheld FlexConnect torch head
Order KP5850-25



FlexCut PRO Mechanized FlexConnect Torch
Includes 25 ft torch cable and Lincoln Electric's patented mechanized FlexConnect torch head
Order KP5852-25



125A Drag Cutting Consumable Kit
Full consumable kit for handheld plasma cutting at 125A
Order KP5829-125

FLEXCUT TORCH BREAKDOWN

P/N	Description	FlexConnect Head	FlexConnect Cable
KP5848-12-5	FlexCut PRO 35 Air Torch - 12.5 FT	N/A	N/A
KP5849-25	FlexCut PRO Handheld Torch - 25 FT	N/A	N/A
KP5849-50	FlexCut PRO Handheld Torch - 50 FT	N/A	N/A
KP5850-25	FlexCut PRO Handheld FlexConnect Torch - 25 FT	KP5855-1	KP5839-25
KP5850-50	FlexCut PRO Handheld FlexConnect Torch - 50 FT	KP5855-1	KP5839-50
KP5852-25	FlexCut PRO Mechanized FlexConnect Torch - 25 FT	KP5853-1	KP5840-25
KP5852-50	FlexCut PRO Mechanized FlexConnect Torch - 50 FT	KP5853-1	KP5840-50

FLEXCONNECT TORCH HEADS

Part Number	Description
KP5853-1	FlexCut PRO FlexConnect Standard Mechanized Torch Head
KP5854-1	FlexCut PRO FlexConnect Mini Mechanized Torch Head
KP5855-1	FlexCut PRO FlexConnect 75° Handheld Torch Head
KP5856-1	FlexCut PRO FlexConnect 15° Handheld Torch Head
KP5838-1	FlexCut PRO FlexConnect Extended Reach Torch Head
KP5920-1	FlexCut PRO XL Extended Reach Torch Head

PRODUCT SPECIFICATIONS

Product Name	Product Number	Package Type	Input Power Voltage/Phase/ Hertz	Rated Output Current/Voltage/ Duty Cycle	Recommended Circuit Breaker	Output Range	Engine Drive Auxiliary Power Requirement	Gas Pressure Required	Dimensions H x W x D in (mm)	Net Weight lb (kg)
FlexCut 125	K5828-H	Handheld	400-600/3/50/60	100% 125 A 400-600 V 3-PH	50A	30A-125A	40kW for 125A	90-130 psi	27.2 (691)	90.6 (41)
	K5828-M	Mechanized							11.5 (292.1)	
	K5828-PS	Power Source Only							18.6 (472)	

For best cutting results with Lincoln Electric® equipment, always use Lincoln Electric consumables. Visit www.lincolnelectric.com for more details.

CUSTOMER ASSISTANCE POLICY

The business of Lincoln Electric is manufacturing and selling high quality welding equipment, automated welding systems, consumables, cutting equipment and EV charging systems. Our challenge is to meet the needs of our customers, who are experts in their fields, and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or technical information about their use of our products. Our employees respond to inquiries to the best of their ability based on information and specifications provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment, or to provide engineering advice in relation to a specific situation or application. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or communications. Moreover, the provision of such information or technical information does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or technical information, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose or any other equivalent or similar warranty is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the definition of specifications, and the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

